

AC Axial Fans

W**200 Ø 225 x 225 x 80 mm



- External-single-phase motor.*
- External-current motor.**
- Integrated thermal monitor.
- Fan housing of die-cast aluminium.
- Impeller of sheet steel, welded onto rotor.
- Air exhaust over struts. Rotational direction CCW looking at rotor.
- Connection leads
- W2E 200: wired with capacitor on terminal strip.
- W4S 200: terminal strip.
- Mass 2000 g.

ebm-papst • Muldingen

Nominal Data	Air Flow	Air Flow	Nominal Voltage	Frequency	Noise		Gleitlager Ball Bearings	Power Input	Nominal Speed	Temperature Range	Service Life L ₁₀ at 40 °C	at t _{max}	Diagram
Type	m ³ /h	CFM	V DC	Hz	dB(A)	Bel	□/■	Watt	min ⁻¹	°C	Hours	Hours	
W2E 200-HK86-01*	1030	606.2	115	60	61	4.1	■	80.0	2800	-15...+65	60 000 / 58 000		2
W2E 200-HK38-01*	925	544.4	230	50	59	4.6	■	64.0	2550	-15...+60	63 000 / 60 000		2
W4S 200-HK04-01**	450	264.9	230	50	40	5.0	■	30.0	1370	-15...+70	85 000 / 80 000		1

